

COLLAK

Adhesivos y Selladores

COLLAK, S.A. – C/. França, 3 – Pol. Ind. Pla de Llerona – 08520 Les Franqueses del Vallès – NIF A08344897
Tel.: (+34) 93 849 44 33 – Fax: (+34) 93 849 22 77 – E-mail: collak@collak.com – www.collak.com

09/11-Lubritot-v1.0

COLLAK LUBRITOT

Silicon grease

1. DESCRIPTION

Lubrication of joints with or without sliding rubbers, bearings, wheels and elements plastic/plastic or plastic/metal. It makes easier the displacement of electrical cables within the protective tubes. It can also be used as security filling paste for electrical conductions tubes.

2. APLICATIONS

Resistant to humid atmospheres. It does not resist to solvents. Excellent dielectric properties. In case of fire, the resultant ashes are formed by silicic anhydride that, by their high insulating power, avoid formation of shorts circuits. Nontoxic product.

PROPIEDADES FÍSICAS	
Colour	Translucent
Density	1.04 g/ml
Solids	100%
Flammable point	> 232 °C

3. INSTRUCTIONS FOR USE

Rest of fluid can be cleaned using a piece of cloth moistened with a solvent that do not damage the dirty surface.

4. PACKAGING

135 g tubes. 25 units per carton.

5. HEALTH & SAFETY

Avoid contact with eyes, mouth, etc. Keep and use it in well-ventilated places. For further information, please read the Safety Data Sheet of our product available upon request.

All data and recommendations given in this Product Data Sheet are given in good faith and based upon information, which we believe to be reliable, but they are made without any representation of guarantee or warranty or accuracy and are made with reservation of all rights. We reserve the right to modify specifications at all times. User should be aware of the current developments of the above-mentioned product. No liability regarding application or circumstances during application can be accepted.