



SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores 
COLLAK R-7766E	
Version 1.1 Revision date: 28/01/2021	Page 1 of 13 Print date: 28/01/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: COLLAK R-7766E

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Adhesive

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **COLLAK, S.A.**
Address: C/ FRANCIA Nº 3 - POL. LLERONA
City: LES FRANQUESES DEL VALLÈS
Province: BARCELONA
Telephone: 93 849 44 33
Fax: 93 849 22 77
E-mail: collak@collak.com
Web: www.collak.com

1.4 Emergency telephone number: 93 849 44 33 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

- Asp. Tox. 1 : May be fatal if swallowed and enters airways.
- Flam. Liq. 2 : Highly flammable liquid and vapour.
- Repr. 2 : Suspected of damaging fertility or the unborn child.
- Skin Irrit. 2 : Causes skin irritation.
- Skin Sens. 1 : May cause an allergic skin reaction.
- STOT RE 2 : May cause damage to organs through prolonged or repeated exposure.
- STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:



Danger

H statements:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

P statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 2 of 13 Print date: 28/01/2021	

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P321	Specific treatment (see ... on this label).
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use... to extinguish.

Contains:

Cloroprene polymer

toluene

butanone, ethyl methyl ketone

naphtha (petroleum), hydrotreated light, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20o C to 190o C (– 4oF to 374oF).]

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.



Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-XXXX	[1] toluene	20 - 50 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - Skin Irrit. 2, H315 - STOT RE 2 *, H373 ** - STOT SE 3, H336	-
Index No: 649-328-00-1 CAS No: 64742-49-0 EC No: 265-151-9 Registration No: 01-2119475133-43-XXXX	naphtha (petroleum), hydrotreated light, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20o C to 190o C (– 4oF to 374oF).] (contains less than 0,1 % w/w benzene)	10 - 50 %	Asp. Tox. 1, H304	-
CAS No: 9010-98-4	Cloroprene polymer	1 - 25 %	Skin Sens. 1, H317	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone, ethyl methyl ketone	1 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 3 of 13 Print date: 28/01/2021	

CAS No: 128-37-0 Registration No: 01-2119565113-46-XXXX	2,6-Di-ter-butyl-p-cresol	0.1 - 0.25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-
--	---------------------------	--------------	---	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* ** ** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.



Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLAK R-7766E		
Version 1.1 Revision date: 28/01/2021	Page 4 of 13 Print date: 28/01/2021	

During a fire and depending on its magnitude the following may occur:
- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.


7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 5 of 13 Print date: 28/01/2021	

7.3 Specific end use(s).
General use in industry

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
toluene	108-88-3	European Union [1]	Eight hours	50 (skin)	192 (skin)
			Short term	100 (skin)	384 (skin)
		United Kingdom [2]	Eight hours	50	191
			Short term	100	384
		Éire [3]	Eight hours	50	192
			Short term	100	384
		United States [4] (Cal/OSHA)	Eight hours	10	
			Short term	150 (Ceiling) 500	
		United States [5] (NIOSH)	Eight hours	100	
			Short term	150	
		United States [6] (OSHA)	Eight hours	200	
			Short term	300 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 [10 min]	
butanone, ethyl methyl ketone	78-93-3	European Union [1]	Eight hours	200	600
			Short term	300	900
		United Kingdom [2]	Eight hours	200	600
			Short term	300	899
		Éire [3]	Eight hours	200	600
			Short term	300	900
		United States [4] (Cal/OSHA)	Eight hours	200	
			Short term	300	
		United States [5] (NIOSH)	Eight hours	200	
			Short term	300	
		United States [6] (OSHA)	Eight hours	200	590
			Short term		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.



[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
toluene CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 6 of 13 Print date: 28/01/2021	

	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	8,13 (mg/kg bw/day)
naphtha (petroleum), hydrotreated light, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction With hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C4 through C11 and boiling in the range of approximately minus 20o C to 190o C (- 4oF to 374oF).] CAS No: 64742-49-0 EC No: 265-151-9	DNEL (Workers)	Inhalation, Long-term, Systemic effects	3,25 (mg/m ³)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m ³)



DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
toluene CAS No: 108-88-3 EC No: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)
	STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)
	butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	aqua (freshwater)
aqua (marine water)		55,8 (mg/L)
Soil		22,5 (mg/kg soil dw)
aqua (intermittent releases)		55,8 (mg/L)

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 7 of 13 Print date: 28/01/2021	






	STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
	oral (Hazard for predators)	1000 (mg/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.



8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Adhesive		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLAK R-7766E		
Version 1.1 Revision date: 28/01/2021	Page 8 of 13 Print date: 28/01/2021	

CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Yellow viscous liquid
Colour: Caramelo
Odour: Characteristic to ketones and hydrocarbons
Odour threshold: N.A./N.A.
pH: No applicable
Melting point: N.A./N.A.
Boiling Point: 56 °C
Flash point: -32 °C
Evaporation rate: Sin determinar
Inflammability (solid, gas): Highly flammable
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: Sin determinar
Vapour density: Sin determinar
Relative density: 0,80-0,90
Solubility: N.A./N.A.
Liposolubility: In most of organic solvents
Hydrosolubility: Partially soluble
Partition coefficient (n-octanol/water): Sin determinar
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: 60 s (Copa Ford, Nº8, 20°C)
Explosive properties: Air/vapour mixture are explosive
Oxidizing properties: No applicable

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.
Blink: N.A./N.A.
Kinematic viscosity: N.A./N.A.
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.



At high temperatures can occur pyrolysis and dehydrogenation.

10.4 Conditions to avoid.

Avoid the following conditions:
- Heating.
- High temperature.

10.5 Incompatible materials.

Avoid the following materials:
- Acids.
- Bases.
- Oxidizing agents.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 
COLLAK R-7766E	Adhesivos y Selladores
Version 1.1 Revision date: 28/01/2021	Page 9 of 13 Print date: 28/01/2021

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard;



Product classified:

Aspiration toxicity, Category 1: May be fatal if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
Version 1.1 Revision date: 28/01/2021	Page 10 of 13 Print date: 28/01/2021	

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
toluene CAS No: 108-88-3 EC No: 203-625-9	2,73	-	-	Low
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	0,29	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.



Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLAK R-7766E		Version 1.1 Revision date: 28/01/2021

14.1 UN number.

UN No: UN1133

14.2 UN proper shipping name.

Description:

ADR: UN 1133, ADHESIVES, 3, PG II, (D/E)

IMDG: UN 1133, ADHESIVES, 3, PG II

ICAO/IATA: UN 1133, ADHESIVES, 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 33

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 80,994 %

VOC content: 647,949 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b



The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores 
COLLAK R-7766E	
Version 1.1 Revision date: 28/01/2021	Page 12 of 13 Print date: 28/01/2021

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Repr. 2 : Reproductive toxicant, Category 2
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Change in the hazard classification (SECTION 2.1).
- Changes in the composition of the product (SECTION 3.2).
- Modification of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of ecological information values (SECTION 12.3).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:



Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLAK R-7766E		
Version 1.1 Revision date: 28/01/2021	Page 13 of 13 Print date: 28/01/2021	

PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.