

COLLAK MS-646

ELASTIC ADHESIVE FOR ARTIFICIAL GRASS

1. DESCRIPTION

- Durable elastic adhesion
- Sound reduction
- Solvent and isocyanates free
- Indoor and outdoor use

2. APLICATIONS

Suitable adhesive for bonding artificial grass in terraces, balcony, leisure areas, decoration, et..

Can be used on absorbent and non-absorbent substrates.

No priming required for most substrates. Very good weathering, chemical and ageing properties.

3. CARACTERÍSTICAS

Color	Green	Waiting time	None
Consistency	Paste	Working time	30 – 45 min
Density	1,50 g/ml	Transitable after	24 hours
Yield (g/m ²)	800-1200	Temperature resistance	-30 to +80°C

4. INSTRUCTIONS FOR USE

Surfaces must be firm, consistent, clean and dust and grease free according to DIN 18 385. Remove any residual adhesive from the surface. Sanded down of non-absorbent substrates such as ceramic or terrazzo floors is recommended. Surfaces with humidity above 3.5% must be previously primed.

Apply the adhesive with a suitable notched trowel. Set immediately the wood flooring over the wet adhesive.

It is not recommended to apply the adhesive if the floor temperature is under 15 °C and relative humidity upon 75%.

Clean the tools with alcohol immediately after use. Dry adhesive must be remove mechanically.

5. PACKING

Metallic buckets of 1 kg and 4 Kg.

6. STORAGE

Can be stored for 12 months in closed (unopened) container in a dry place at temperatures between +5°C and 30°C. Tightly close opened buckets and use them up as soon as possible.

7. CAUTIONS

Keep away from children. Avoid contact with eyes and skin. Safety data sheet is available on demand.

Every endeavour has been made to ensure that the information given herein is true and reliable, but is given only for the guidance of our customers. Collak, S.A. cannot accept any responsibility for loss or damage or infringements of patent rights that may result from the use of the information, due the possibility of variations of processing or working conditions are outside our control. Users are advised to confirm the suitability of the products with their own tests. Our technical service is at customer's disposal for any conference, explanation or advise.