

## COLLAK WA-15

### Aqueous primer for absorbent and non-absorbent substrates

#### 1. DESCRIPTION

Dispersion aqueous primer without solvents.

#### 2. APPLICATION

Dispersion aqueous primer for absorbent and non-absorbent substrates before adding levelling products or coatings to be adhered.

#### 3. TECHNICAL DATA

PROPERTIES	VALUES
Colour	Orange
Specific gravity (20°C)	0.90 – 1.00 g/mL
Viscosity (Brookfield HBT Sp1, 20 rpm, 20 °C)(cps)	700-900 cps
Yield on non-absorbent substrates (diluted 1:1 with water (%))	50-150 g/m <sup>2</sup>
Yield on absorbent substrates (diluted 1:4 with water (%))	40-60 g/ m <sup>2</sup>

#### 5. USE

Surface must be clean, dry, even and free from grease. Substrates must comply with the requirements of DIN 18365. Apply a continuous layer of the adhesive on the floor with a brush or roller.

On very absorbent substrates is recommended to dilute with one or two parts of water in order to get penetration enough on them. On firm and non-porous surfaces must not be diluted.

Dry time depends on the porosity of substrates and weathering conditions. It could take several hours. Do not apply at temperatures lower than +5°C.

Dilution and contaminated surfaces with primer must be done with water. The dried primer can be cleaned with Collak D-0.

#### 4. CLEANING

Clean tools or excess adhesive with water. The dried primer can be cleaned with Collak D-0.

#### 5. PACKAGING AND STORAGE

All data and recommendations given in this Product Data Sheet are given in good faith and based upon information, which we believe to be reliable, but they are made without any representation of guarantee or warranty or accuracy and are made with reservation of all rights. We reserve the right to modify specifications at all times. User should be aware of the current developments of the above-mentioned product. No liability regarding application or circumstances during application can be accepted.

# COLLAK

## Adhesivos y Selladores



COLLAK, S.A. – C/. França, 3 – Pol. Ind. Pla de Llerona – 08520 Les Franqueses del Vallès – NIF A08344897  
Tel.: (+34) 93 849 44 33 – Fax: (+34) 93 849 22 77 – E-mail: [collak@collak.com](mailto:collak@collak.com) – [www.collak.com](http://www.collak.com)

In 5 and 16 kg cans. The shelf life of the product is estimated on 12 months in the closed original packaging stored at normal ambient conditions (e.g. 20°C and 55% relative humidity).

All data and recommendations given in this Product Data Sheet are given in good faith and based upon information, which we believe to be reliable, but they are made without any representation of guarantee or warranty or accuracy and are made with reservation of all rights. We reserve the right to modify specifications at all times. User should be aware of the current developments of the above-mentioned product. No liability regarding application or circumstances during application can be accepted.