

## COLLAK WA-1010

### CARPET ADHESIVE

#### 1. DESCRIPTION

Water based dispersion adhesive, solvent and odour free.  
High performance. Strong initial tack. Low volatile organic compounds content.

#### 2. APLICATION

High strength adhesive for textile coverings on porous substrates: tufted coverings with textile and latex foamed backings, composite coverings with textile or non-woven backings, etc.

#### 3. TECHNICAL DATA

PROPERTIES	VALUES
Colour	Creamy white
Aspect	Paste
Density (20°C)	1,43 – 1,46 g/ml
Coverage Spatula A2 Spatula B1	350 g/m <sup>2</sup> 450 g/m <sup>2</sup>
Open time <sup>(1)</sup>	Porous carpets: Aprox. 5-10 minutes Non porous carpets: Aprox. 10-15 minutes
Working time <sup>(1)</sup>	Approx. 20-30 minutes
Final strength <sup>(1)</sup>	Approx. 72 hours
Temperature resistance after curing	Max. 50° C. For use on underfloor heating

<sup>(1)</sup>The above times are based on normal climatic conditions (23°C/50% rel. humidity). Other climatic conditions can result in a lengthening or reduction of curing and drying times.

#### 4. USES

Substrates must comply with the requeriments of DIN 18365. In particular they must be clean, free from structural defects, firm, dry an free of substances which may impair adhesion.

##### 1. Porous carpets

After a short open time of approx. 5-10 minutes, place the covering material into the still wet adhesive bed, taking care to avoid air pockets and carefully rub it down to ensure good wetting of the back.

# COLLAK

## Adhesivos y Selladores



COLLAK, S.A. – C/. França, 3 – Pol. Ind. Pla de Llerona – 08520 Les Franqueses del Vallès – NIF A08344897  
Tel.: (+34) 93 849 44 33 – Fax: (+34) 93 849 22 77 – E-mail: [collak@collak.com](mailto:collak@collak.com) – [www.collak.com](http://www.collak.com)

07/17-WA-1010-v1.0

### **2. Non porous carpet**

Apply the adhesive with a notched trowel, wait 10-15 minutes and place the covering material taking care to avoid air pockets and carefully rub it down to ensure good wetting of the back.

Do not install floor coverings at floor temperatures below 15°C and over 35°C or at relative humidity above 75%.

Follow floor covering manufacturers product installation instructions. Acclimatize materials previous to the installation.

Clean tools with soap and water immediately after use.

### **5. PACKAGING AND STORAGE**

- In plastic buckets of 20 Kg.

### **6. PRODUCT SAFETY**

It is not a toxic or flammable product. For more information see material safety data sheet.

All data and recommendations given in this Product Data Sheet are given in good faith and based upon information, which we believe to be reliable, but they are made without any representation of guarantee or warranty or accuracy and are made with reservation of all rights. We reserve the right to modify specifications at all times. User should be aware of the current developments of the above-mentioned product. No liability regarding application or circumstances during application can be accepted.