

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 2.0 Revision date: 15/10/2021	Page 1 of 11 Print date: 15/10/2021	

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: COLLE AM BLANC 125 mL

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Tixotropic adhesive

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **COLLAK, S.A.**
Address: C/ FRANCIA Nº 3 - POL. LLERONA
City: 08520 - LES FRANQUESES DEL VALLÈS
Province: BARCELONA
Telephone: 93 849 44 33
Fax: 93 849 22 77
E-mail: collak@collak.com
Web: www.collak.com

1.4 Emergency telephone number: 93 849 44 33 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

- Acute Tox. 4 : Harmful if swallowed.
- Carc. 2 : Suspected of causing cancer.
- Eye Dam. 1 : Causes serious eye damage.
- Flam. Liq. 2 : Highly flammable liquid and vapour.
- Skin Irrit. 2 : Causes skin irritation.
- STOT SE 3 : May cause respiratory irritation.
- STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

P statements:

- P101 If medical advice is needed, have product container or label at hand.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 2.0 Revision date: 15/10/2021	Page 2 of 11 Print date: 15/10/2021	

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P405	Store locked up.
P501	Dispose of contents/container to a properly place habilitated by local authorities.

EUH statements:

EUH019	May form explosive peroxides.
EUH208	Contains dibutyl tin carboxylate. May produce an allergic reaction.

Contains:

Cyclohexanone
tetrahydrofuran

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.


3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-025-00-0 CAS No: 109-99-9 EC No: 203-726-8 Registration No: 01-2119444314-46-XXXX	[1] tetrahydrofuran	25 - 75 %	Acute Tox. 4, H302 - Carc. 2, H351 - Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H335 - STOT SE 3, H336	Eye Irrit. 2, H319: C ≥ 25 % STOT SE 3, H335: C ≥ 25 % STOT SE 3, H336: C ≥ 25%
Index No: 606010007 CAS No: 108-94-1 EC No: 203-631-1 Registration No: 01-2119453616-35-xxxx	Cyclohexanone	10 - 25 %	Acute Tox. 4, H312 - Acute Tox. 4, H332 - Acute Tox. 4, H302 - Eye Dam. 1, H318 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 77-58-7 EC No: 201-039-8 Registration No: 01-2119496068-27-XXXX	dibutyl tin carboxylate	0.1 - 0.25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Muta. 2, H341 - Repr. 1B, H360 - Skin Corr. 1C, H314 - Skin Sens. 1, H317 - STOT RE 1, H372 - STOT SE 1, H370	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLE AM BLANC 125 mL		
Version 2.0 Revision date: 15/10/2021	Page 3 of 11 Print date: 15/10/2021	

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Long-term chronic exposure may result in injury to certain organs or tissues.

Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.



Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 
COLLE AM BLANC 125 mL	
Version 2.0 Revision date: 15/10/2021	Page 4 of 11 Print date: 15/10/2021

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):


Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

7.3 Specific end use(s).

Carpentry of rigid PVC

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 2.0 Revision date: 15/10/2021	Page 5 of 11 Print date: 15/10/2021	

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
tetrahydrofuran	109-99-9	European Union [1]	Eight hours	50 (skin)	150 (skin)
			Short term	100 (skin)	300 (skin)
		United Kingdom [2]	Eight hours	50	150
			Short term	100	300
		Éire [3]	Eight hours	50	150
			Short term	100	300

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
tetrahydrofuran CAS No: 109-99-9 EC No: 203-726-8	DNEL (Workers)	Inhalation, Long-term, Local effects	150 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	150 (mg/m ³)




DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.


8.2 Exposure controls.



Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Tixotropic adhesive		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 2.0 Revision date: 15/10/2021	Page 6 of 11 Print date: 15/10/2021	

Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.	
Skin protection:		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: White liquid
 Colour: Blanco
 Odour: Characteristic of ketones
 Odour threshold: N.A./N.A.
 pH: N.A./N.A.
 Melting point: N.A./N.A.
 Boiling Point: 66 °C
 Flash point: -10 °C
 Evaporation rate: Not determined
 Inflammability (solid, gas): Highly flammable
 Lower Explosive Limit: N.A./N.A.
 Upper Explosive Limit: N.A./N.A.
 Vapour pressure: 173 mbar (at 20°C)
 Vapour density: Not determined
 Relative density: 0,950 g/cm³ (at 20°C)
 Solubility: N.A./N.A.
 Liposolubility: Not determined
 Hydrosolubility: partible soluble
 Partition coefficient (n-octanol/water): Not determined
 Auto-ignition temperature: N.A./N.A.
 Decomposition temperature: N.A./N.A.
 Viscosity: 2500-3000 cps
 Explosive properties: Vapour/air mixtures are explosive
 Oxidizing properties: Not applicable

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.
 Blink: N.A./N.A.
 Kinematic viscosity: N.A./N.A.
 N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLE AM BLANC 125 mL		
Version 2.0 Revision date: 15/10/2021	Page 7 of 11 Print date: 15/10/2021	

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

May form explosive peroxides.

At high temperatures can occur pyrolysis and dehydrogenation.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 10.516 mg/kg

ATE (Oral) = 657 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:


Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLE AM BLANC 125 mL		
Version 2.0 Revision date: 15/10/2021	Page 8 of 11 Print date: 15/10/2021	

f) carcinogenicity;
Product classified:
Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity;
Based on available data, the classification criteria are not met.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.


Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLE AM BLANC 125 mL		
Version 2.0 Revision date: 15/10/2021	Page 9 of 11 Print date: 15/10/2021	

Transport document: Airway bill.

14.1 UN number.

UN No: UN1133

14.2 UN proper shipping name.

Description:

ADR: UN 1133, ADHESIVES, 3, PG III, (D/E)

IMDG: UN 1133, ADHESIVES, 3, PG III

ICAO/IATA: UN 1133, ADHESIVES, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 76,15 %

VOC content: 723,425 g/l


Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	COLLAK Adhesivos y Selladores	
Version 2.0 Revision date: 15/10/2021	Page 10 of 11 Print date: 15/10/2021	

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.



Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
 Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
 Acute Tox. 4 : Acute toxicity (Oral), Category 4
 Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
 Carc. 2 : Carcinogen, Category 2
 Eye Dam. 1 : Serious eye damage, Category 1
 Eye Irrit. 2 : Eye irritation, Category 2
 Flam. Liq. 2 : Flammable liquid, Category 2
 Flam. Liq. 3 : Flammable liquid, Category 3
 Muta. 2 : Mutagen, Category 2
 Repr. 1B : Reproductive toxicant, Category 1B
 Skin Corr. 1C : Skin Corrosive, Category 1C
 Skin Irrit. 2 : Skin irritant, Category 2
 Skin Sens. 1 : Skin sensitiser, Category 1
 STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
 STOT SE 1 : Specific target organ toxicity following a single exposure, Category 1
 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification of the symptoms (SECTION 4.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Elimination of exposure data (SECTION 8.1).
- Modification of exposure data (SECTION 8.1).
- Modification of the information of the stability and reactivity conditions (SECTION 10.3).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).
- Change in the hazard classification (SECTION 11.1).
- Elimination of ecological information values (SECTION 12.3).
- Elimination of abbreviations and acronyms (SECTION 16).

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2015/830)	 COLLAK Adhesivos y Selladores	
COLLE AM BLANC 125 mL		
Version 2.0 Revision date: 15/10/2021	Page 11 of 11 Print date: 15/10/2021	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.